



PRODUKTBESCHREIBUNG

- » Als Pilot- und Kernlochbohrer einsetzbar
- » Hochleistungs-Bohrer mit parabolischem Nutenprofil

MATERIAL

- » HSS, TiN-beschichtet

Inhalt	Nr.	EUR
d = 1, 1.5, 2, 2.5, 3, 3.3, 3.5, 4, 4.2, 4.5, 5, 5.5, 6, 6.5, 6.8, 7, 7.5, 8, 8.5, 9, 9.5, 10, 10.2, 10.5	WZB 30213/Set1-10KB	< >
d = 1, 1.1, 1.2, 1.3, 1.4, 1.5, 1.6, 1.7, 1.8, 1.9, 2, 2.1, 2.2, 2.3, 2.4, 2.5, 2.6, 2.7, 2.8, 2.9, 3, 3.1, 3.2, 3.3, 3.4, 3.5, 3.6, 3.7, 3.8, 3.9, 4, 4.1, 4.2, 4.3, 4.4, 4.5, 4.6, 4.7, 4.8, 4.9, 5, 5.1, 5.2, 5.3, 5.4, 5.5, 5.6, 5.7, 5.8, 5.9	WZB 30213/Set1-5,9	< >
d = 6, 6.1, 6.2, 6.3, 6.4, 6.5, 6.6, 6.7, 6.8, 6.9, 7, 7.1, 7.2, 7.3, 7.4, 7.5, 7.6, 7.7, 7.8, 7.9, 8, 8.1, 8.2, 8.3, 8.4, 8.5, 8.6, 8.7, 8.8, 8.9, 9, 9.1, 9.2, 9.3, 9.4, 9.5, 9.6, 9.7, 9.8, 9.9, 10	WZB 30213/Set6-10	< >

RICHTWERTE BOHREN

WZB 30213	Werkstoff	Festigkeit	Vc ¹ m/min.	≤ d											
				f ² (mm/u)											
				0.5	1	2	2.5	3	4	5	6	8	10	12	14
	1.1730	640 N/mm ²	20	0.008	0.014	0.040	0.050	0.063	0.070	0.080	0.100	0.125	0.150	0.160	0.180
	1.2083	780 N/mm ²	14	0.007	0.012	0.032	0.040	0.050	0.060	0.065	0.080	0.100	0.120	0.130	0.150
	1.2085	1080 N/mm ²	14	0.006	0.011	0.031	0.040	0.045	0.055	0.060	0.075	0.095	0.115	0.125	0.140
	1.2162	660 N/mm ²	16	0.008	0.014	0.040	0.050	0.063	0.070	0.080	0.100	0.125	0.150	0.160	0.180
	1.2311	1080 N/mm ²	12	0.007	0.012	0.032	0.040	0.050	0.060	0.065	0.080	0.100	0.120	0.130	0.150
	1.2312	1080 N/mm ²	16	0.006	0.011	0.031	0.040	0.045	0.055	0.060	0.075	0.095	0.115	0.125	0.140
	1.2316	1010 N/mm ²	10	0.007	0.012	0.032	0.040	0.050	0.060	0.065	0.080	0.100	0.120	0.130	0.150
	1.2343	780 N/mm ²	14	0.007	0.012	0.032	0.040	0.050	0.060	0.065	0.080	0.100	0.120	0.130	0.150
	1.2379	780 N/mm ²	12	0.008	0.014	0.040	0.050	0.063	0.070	0.080	0.100	0.125	0.150	0.160	0.180
	1.2767	830 N/mm ²	14	0.008	0.014	0.039	0.049	0.062	0.069	0.079	0.095	0.120	0.145	0.155	0.180
	1.2842	775 N/mm ²	16	0.007	0.012	0.032	0.040	0.050	0.060	0.065	0.080	0.100	0.120	0.130	0.150

1) Vc: Schnittgeschwindigkeit (m/min.)

2) f: Vorschub pro Umdrehung (mm/u)

- » Ab 5 x d nur mit Entspanzyklus weiterbohren

- » Zentrierung erforderlich

i Weitere Materialien und Schnittwerte finden Sie im Schnittdaten-Kalkulator

HSS BOHRER DIN 338

WZB 30213




PRODUKTBESCHREIBUNG

- » Als Pilot- und Kernlochbohrer einsetzbar
- » Hochleistungs-Bohrer mit parabolischem Nutenprofil

MATERIAL

- » HSS, TiN-beschichtet



l	l1	d	Nr.	EUR
22	6	0,5	WZB 30213/ 0,5	<>
24	7	0,6	WZB 30213/ 0,6	<>
28	9	0,7	WZB 30213/ 0,7	<>
30	10	0,8	WZB 30213/ 0,8	<>
32	11	0,9	WZB 30213/ 0,9	<>
34	12	1	WZB 30213/ 1	<>
36	14	1,1	WZB 30213/ 1,1	<>
38	16	1,2	WZB 30213/ 1,2	<>
38	16	1,3	WZB 30213/ 1,3	<>
40	18	1,4	WZB 30213/ 1,4	<>
40	18	1,5	WZB 30213/ 1,5	<>
43	20	1,6	WZB 30213/ 1,6	<>
43	20	1,7	WZB 30213/ 1,7	<>
46	22	1,8	WZB 30213/ 1,8	<>
46	22	1,9	WZB 30213/ 1,9	<>
49	24	2	WZB 30213/ 2	<>
49	24	2,1	WZB 30213/ 2,1	<>
53	27	2,2	WZB 30213/ 2,2	<>
53	27	2,3	WZB 30213/ 2,3	<>
57	30	2,4	WZB 30213/ 2,4	<>
57	30	2,5	WZB 30213/ 2,5	<>
57	30	2,6	WZB 30213/ 2,6	<>
61	33	2,7	WZB 30213/ 2,7	<>
61	33	2,8	WZB 30213/ 2,8	<>
61	33	2,9	WZB 30213/ 2,9	<>
61	33	3	WZB 30213/ 3	<>
65	36	3,1	WZB 30213/ 3,1	<>
65	36	3,2	WZB 30213/ 3,2	<>
65	36	3,3	WZB 30213/ 3,3	<>
70	39	3,4	WZB 30213/ 3,4	<>
70	39	3,5	WZB 30213/ 3,5	<>
70	39	3,6	WZB 30213/ 3,6	<>
70	39	3,7	WZB 30213/ 3,7	<>

l	l1	d	Nr.	EUR
75	43	3,8	WZB 30213/ 3,8	<>
75	43	3,9	WZB 30213/ 3,9	<>
75	43	4	WZB 30213/ 4	<>
75	43	4,1	WZB 30213/ 4,1	<>
75	43	4,2	WZB 30213/ 4,2	<>
80	47	4,3	WZB 30213/ 4,3	<>
80	47	4,4	WZB 30213/ 4,4	<>
80	47	4,5	WZB 30213/ 4,5	<>
80	47	4,6	WZB 30213/ 4,6	<>
80	47	4,7	WZB 30213/ 4,7	<>
86	52	4,8	WZB 30213/ 4,8	<>
86	52	4,9	WZB 30213/ 4,9	<>
86	52	5	WZB 30213/ 5	<>
86	52	5,1	WZB 30213/ 5,1	<>
86	52	5,2	WZB 30213/ 5,2	<>
86	52	5,3	WZB 30213/ 5,3	<>
93	57	5,4	WZB 30213/ 5,4	<>
93	57	5,5	WZB 30213/ 5,5	<>
93	57	5,6	WZB 30213/ 5,6	<>
93	57	5,7	WZB 30213/ 5,7	<>
93	57	5,8	WZB 30213/ 5,8	<>
93	57	5,9	WZB 30213/ 5,9	<>
93	57	6	WZB 30213/ 6	<>
101	63	6,1	WZB 30213/ 6,1	<>
101	63	6,2	WZB 30213/ 6,2	<>
101	63	6,3	WZB 30213/ 6,3	<>
101	63	6,4	WZB 30213/ 6,4	<>
101	63	6,5	WZB 30213/ 6,5	<>
101	63	6,6	WZB 30213/ 6,6	<>
101	63	6,7	WZB 30213/ 6,7	<>
109	69	6,8	WZB 30213/ 6,8	<>
109	69	6,9	WZB 30213/ 6,9	<>
109	69	7	WZB 30213/ 7	<>

I	I1	d	Nr.	EUR
109	69	7,1	WZB 30213/ 7,1	<>
109	69	7,2	WZB 30213/ 7,2	<>
109	69	7,3	WZB 30213/ 7,3	<>
109	69	7,4	WZB 30213/ 7,4	<>
109	69	7,5	WZB 30213/ 7,5	<>
117	75	7,6	WZB 30213/ 7,6	<>
117	75	7,7	WZB 30213/ 7,7	<>
117	75	7,8	WZB 30213/ 7,8	<>
117	75	7,9	WZB 30213/ 7,9	<>
117	75	8	WZB 30213/ 8	<>
117	75	8,1	WZB 30213/ 8,1	<>
117	75	8,2	WZB 30213/ 8,2	<>
117	75	8,3	WZB 30213/ 8,3	<>
117	75	8,4	WZB 30213/ 8,4	<>
117	75	8,5	WZB 30213/ 8,5	<>
125	81	8,6	WZB 30213/ 8,6	<>
125	81	8,7	WZB 30213/ 8,7	<>
125	81	8,8	WZB 30213/ 8,8	<>
125	81	8,9	WZB 30213/ 8,9	<>
125	81	9	WZB 30213/ 9	<>
125	81	9,1	WZB 30213/ 9,1	<>
125	81	9,2	WZB 30213/ 9,2	<>
125	81	9,3	WZB 30213/ 9,3	<>
125	81	9,4	WZB 30213/ 9,4	<>
125	81	9,5	WZB 30213/ 9,5	<>

I	I1	d	Nr.	EUR
133	87	9,6	WZB 30213/ 9,6	<>
133	87	9,7	WZB 30213/ 9,7	<>
133	87	9,8	WZB 30213/ 9,8	<>
133	87	9,9	WZB 30213/ 9,9	<>
133	87	10	WZB 30213/10	<>
133	87	10,1	WZB 30213/10,1	<>
133	87	10,2	WZB 30213/10,2	<>
133	87	10,3	WZB 30213/10,3	<>
133	87	10,4	WZB 30213/10,4	<>
133	87	10,5	WZB 30213/10,5	<>
133	87	10,6	WZB 30213/10,6	<>
142	94	10,7	WZB 30213/10,7	<>
142	94	10,8	WZB 30213/10,8	<>
142	94	10,9	WZB 30213/10,9	<>
142	94	11	WZB 30213/11	<>
142	94	11,5	WZB 30213/11,5	<>
142	94	11,6	WZB 30213/11,6	<>
142	94	11,8	WZB 30213/11,8	<>
151	101	11,9	WZB 30213/11,9	<>
151	101	12	WZB 30213/12	<>
151	101	12,5	WZB 30213/12,5	<>
151	101	13	WZB 30213/13	<>
160	108	13,5	WZB 30213/13,5	<>
160	108	14	WZB 30213/14	<>