

### PRODUCT DESCRIPTION

Universally usable, mineral oil free cutting oil, suitable for the machining and forming of steel and non-ferrous metals. The high-quality mixture with EP additives enables economically efficient use, reduces tool wear and prevents the formation of built-up edges.


### ADVANTAGES

- » Optimally suited for minimum quantity lubrication
- » For high-quality surfaces and high dimensional accuracy
- » Machining of non-ferrous metal possible
- » Chlorine and silicone-free - no hazardous substances

### APPLICATION

Hand processing by means of a spray bottle or as circulating oil. Also suitable for use as minimum quantity lubrication oil.



Package <sup>1)</sup>	Content	 Pcs. / PU	No.	EUR
Bottle	250ml	1	VKS 20/ 1/ 250	< >
Bottle	250ml	10	VKS 20/10/ 250	< >
Can + bottle	5l	1	VKS 20/ 1/5000	< >

1) Can and lubricator: including VZB 10/250

 Material safety data sheets at each product under [www.meusburger.com](http://www.meusburger.com)

### CHARACTERISTICS

VKS 20	Value	Test procedure
Colour	golden brown	DIN ISO 2049
Flashpoint	> 180 °C	DIN EN ISO 2592
Viscosity	20 mm <sup>2</sup> /s	DIN 51 562
Basis	natural materials	
Density	0.91 g/cm <sup>3</sup>	DIN 51 757