



## DESCRIZIONE DEL PRODOTTO


» Per filettatura metrica ISO a passo fino

## MATERIALE

» HSS-E (5% Co), rivestimento TiN



SW	d3	d5	l	l1	d	P	N°	EUR
2,7	3,5	4,5	70	5	M 5	0,5	WZG 34221/ 5x0,5	< >
3,4	4,5	5,2	80	8	M 6	0,75	WZG 34221/ 6x0,75	< >
4,3	5,5	6	80	8	M 7	1	WZG 34221/ 7x1	< >
4,9	6	7,2	80	8	M 8	0,75	WZG 34221/ 8x0,75	< >
4,9	6	7	90	11	M 8	1	WZG 34221/ 8x1	< >
5,5	7	8	90	11	M 9	1	WZG 34221/ 9x1	< >
5,5	7	9	90	11	M10	1	WZG 34221/10x1	< >
6,2	8	10	90	11	M11	1	WZG 34221/11x1	< >
7	9	10,5	100	16	M12	1,5	WZG 34221/12x1,5	< >
9	11	12,5	100	15	M14	1,5	WZG 34221/14x1,5	< >
9	12	14,5	100	15	M16	1,5	WZG 34221/16x1,5	< >
11	14	16,5	110	16	M18	1,5	WZG 34221/18x1,5	< >
12	16	18,5	125	16	M20	1,5	WZG 34221/20x1,5	< >
14,5	18	20,5	125	16	M22	1,5	WZG 34221/22x1,5	< >
14,5	18	22,5	140	16	M24	1,5	WZG 34221/24x1,5	< >
14,5	18	22	140	22	M24	2	WZG 34221/24x2	< >



## VALORI DI RIFERIMENTO PER I MASCHI A MACCHINA

WZG 341112 WZG 34121 WZG 341215 WZG 34221 WZG 34521	WZG 34123 WZG 341235 WZG 34223 WZG 34523	Materiale	Resistenza	Vc <sup>1</sup> m/min.
		1.1730	640 N/mm <sup>2</sup>	10
		1.2083	780 N/mm <sup>2</sup>	8
		1.2085	1080 N/mm <sup>2</sup>	6
		1.2162	660 N/mm <sup>2</sup>	10
		1.2311	1080 N/mm <sup>2</sup>	6
		1.2312	1080 N/mm <sup>2</sup>	6
		1.2316	1010 N/mm <sup>2</sup>	6
		1.2343	780 N/mm <sup>2</sup>	10
		1.2379	780 N/mm <sup>2</sup>	6
		1.2767	830 N/mm <sup>2</sup>	8
		1.2842	775 N/mm <sup>2</sup>	10

1) Vc: Velocità di taglio (m/min.)

Nel calcolatore dei parametri di taglio potete trovare altri materiali e valori di taglio